FREDREP



COMMERCIAL

MODELS:

2448KW 24hp, 48" Deck 2454KW 24hp, 54" Deck 2460KW 24hp, 60" Deck



The **Falcon HPX** is the new standard in entry-level commercial mowing with high-quality features, robust durability, and operator comfort and convenience.

- **Proven Power –** Equipped with 24 horsepower Kawasaki^{*} FT engines for years of trusted reliability and performance.
- **Deep Deck** The Falcon HPX deck features a deep 10 gauge shell to tackle taller grass with ease.
- **Commercial Drive System** Hydro-Gear ZT-3100 transaxles offer steel-cut gears, charge pumps, and shock valves for extended drivetrain performance.
- **Total Comfort** The padded and over-sized bolstered seat hugs your torso for ultimate comfort.
- **Peer' Turf Xtreme™ Spindles** Maintenance free and constructed of high-strength ductile iron.
- **R.O.P.S.** Roll-over protection system comes standard to keep operators safe.
- **Charge and Mow** Keep your mobile device and accessories charged with a USB charging port.
- **Ready to Accessorize** The Falcon HPX is ready to add a suite of accessories including Springer Forks, suspension seat, OCDC, mulch kit, light kit, striping kit, and more.



Kawasaki" Engines – Reliable power to tackle the toughest jobs



Hydro-Gear^{*} ZT-3100 – Commercial duty drivetrain with serviceable filters



Deep Deck - Deep deck shell to tackle more volume



NYEG

Falcon HPX 2460KW shown



More Traction - Large 22" rear tires with semi-aggressive tread pattern



PEER' Spindles - Maintenance free with Contamination Exclusion Technology



*Unlimited hour limited warranty, see dealer for complete warranty details

FALCON HPX





	48" Deck	54" Deck	60" Deck	
Model	2448KW	2454KW	2460KW	
Engine				
Manufacturer	Kawasaki [®] FT			
Horsepower	24			
Displacement	726cc			
Air-cleaner	2 stage			
Cooling	Air-cooled			
Starter	Electric			
Engine warranty	3-Year			

Drive System	
Dual hydrostatic	Hydro-Gear [®] ZT-3100
Ground speed	8 mph
Parking brake	Integrated in transaxle
Towing capacity	200 lbs

Mower Deck				
Deck size	48"	54"	60"	
Acres/hour*	3.1	3.4	3.8	
Cutting height	1.5" - 5"			
OCDC (operator controlled discharge chute)	Optional accessory (hand-operated)			
Deck height adjustments	Manual lift, 1/2" increments			
Deck engagement	Warner [®] 150 ft-lbs			
Construction	10 ga formed & welded			
Blades	(3) -2.5" × 17"	(3) - 2.5" x 19"	(3) - 2.5" × 20.5"	
Blade tip speed (approximate)	18,500 fpm			
Spindles	1.25" effective diameter machined shaft			
Spindle housings	Peer® Turf Xtreme™ ductile iron (sealed)			
Anti-scalp rollers	3			
Pulleys	7 ga steel c	Vented split 3/8″steel deep groove		

General			
Battery	12 Volt, 300cca		
Digital Display	hour meter, tachometer		
Fuel capacity	5 gallons		
Rear tires	22x11-10 - 350 Mag		
Front tires	13 x 6.5-6		
Frame	Welded 1″ x 2″, 2″ x 2″ tube, 11 ga formed		
Floor-pan	Removable, steel		
Seat	High-back adjustable padded seat w/ armrests		
Springer Forks	Optional accessory		

Dimensions				
Overall height (rollbar down)	51.5″			
Overall height (with optional rollbar up)	71.1"			
Overall width (chute down)	63.6"	69.6"	76″	
Overall width (chute up)	49.2"	55.4"	61.9″	
Overall length	74.1″			
Weight	870 lbs	880 lbs	890 lbs	



(765)-CHOPPER www.dixiechopper.com

*Acres/hour at top speed and 80% efficient. Specifications and cosmetics, while correct at the time of printing, may change without notice. Engine horsepower is provided by the engine manufacturer to be used for comparison only. ©2024 Dixie Chopper. All rights reserved.